


Aluminum Tubular Terminal Ends IS: 8309 (MGALS Series)



Technical Specification

Material: Aluminum IS 5082

Surface: Tin-plated to protect against corrosion

Minimum operating temperature: -50 °C

Maximum operating temperature: 150 °C

Reference standard: Indian Standards

Features

- Annealed material optimizes material and crimping properties
- ETP Electrolytic Grade Copper.
- Tin-plated 5 micron plus to protect against corrosion.
- Crack free crimping.
- Bur free connection surface.
- Lowest millivolt drop for DC current application.
- Simple and safe connection.
- Terminate power cables in high-voltage applications.
- Provided with inspection hole to ensure the conductor has been fully inserted before crimping is done.
- Flat contact surface to avoid hotspot.

Aluminum Tubular Terminal Ends IS: 8309 (MGALS Series)


ALUMINUM TUBULAR TERMINAL ENDS

AS PER IS 8309 : 1993

MATERIAL : ALUMINIUM IS : 5082 :

1998

SURFACE : NATURAL



Size mm ²	E	A	C	D	F	B	K	H	G	J	MG CAT NO.	Crim- ping Tools Code
2.5	3.2	2	5.5	6.6	3.5	7	3	4	4	18	MGALS-151	MG-10
2.5	3.7	2.6	5.5	7	2.9	7	3	4	4	18	MGALS-309	MG-10
4	4.2	2.9	5.5	7.2	2.6	7	3	4	4	18	MGALS-155	MG-10
4	5.2	2.9	5.5	12	1.2	7	4	7	6	23	MGALS-317	MG-10
6	5.2	3.5	5.5	7.5	2	7	4	7	6	24	MGALS-158	MG-10
6	6.5	3.5	5.5	12	1.1	7	4	7	6	24	MGALS-313	MG-10
10	4.2	3.8	6.2	8.4	2.4	7	4	9	8	28	MGALS-159	MG-10
10	6.4	4.4	7.2	9.7	2.8	9	4	9	8	30	MGALS-214	MG-10
10	8.2	4.4	7.2	15	1.8	9	4	9	8	30	MGALS-215	MG-10
16	6.4	5.4	8.3	11.4	2.9	13	4	11	9	37	MGALS-252	MG-50SC
16	8.2	5.4	8.3	11.4	2.9	13	4	11	9	37	MGALS-216	MG-50SC
16	10.2	5.4	8.3	18	1.8	13	4	11	9	37	MGALS-217	MG-50SC

Aluminum Tubular Terminal Ends IS: 8309 (MGALS Series)

Size mm ²	E	A	C	D	F	B	K	H	G	J	MG CAT NO.	Crim- ping Tools Code
25	6.4	7	9.7	13.7	2.7	16	7	11	10	44	MGALS-253	MG-50SC
25	8.2	7	9.7	13.7	2.7	16	7	11	10	44	MGALS-218	MG-50SC
25	10.2	7	9.7	18	1.7	16	7	11	10	44	MGALS-219	MG-50SC
25	12.7	7	9.7	18	1.7	16	7	11	10	44	MGALS-220	MG-50SC
35	6.4	8	10.8	15.4	2.8	18	7	11	11	47	MGALS-254	MG-50SC
35	8.2	8	10.8	15.4	2.8	18	7	11	11	47	MGALS-221	MG-50SC
35	10.2	8	10.8	20	2.1	18	7	11	11	47	MGALS-222	MG-50SC
50	8.2	9.3	13	18.3	3.7	22	8	13	11	54	MGALS-255	MG-50SC
50	10.2	9.3	13	23	2.8	22	8	13	11	54	MGALS-312	MG-50SC
50	12.7	9.3	13	23	2.8	22	8	13	11	54	MGALS-224	MG-50SC
70	8.2	11.4	15.6	22.3	4.4	26	8	13	13	60	MGALS-256	MG-120
70	10.2	11.4	15.6	22.3	4.4	26	8	13	13	60	MGALS-225	MG-120
70	12.7	11.4	15.6	22.3	4.4	26	8	13	13	60	MGALS-226	MG-120
95	10.2	13	17.4	24.6	4.2	28	8	14	14	64	MGALS-227	MG-120
95	12.7	13	17.4	24.6	4.2	28	8	14	14	64	MGALS-228	MG-120
95	16.2	13	17.4	24.6	4.2	28	8	14	14	64	MGALS-229	MG-120
120	10.2	14.7	19.6	28.2	4.6	32	11	15	15	73	MGALS-257	MG-120
120	12.7	14.7	19.6	28.2	4.6	32	11	15	15	73	MGALS-230	MG-120
120	16.2	14.7	19.6	28.2	4.6	32	11	15	15	73	MGALS-231	MG-120
150	10.2	16.5	21.5	30.9	5	34	11	17	17	79	MGALS-258	MG-300H
150	12.7	16.5	21.5	30.9	5	34	11	17	17	79	MGALS-232	MG-300H

Aluminum Tubular Terminal Ends IS: 8309 (MGALS Series)

Size mm ²	E	A	C	D	F	B	K	H	G	J	MG CAT NO.	Crim- ping Tools Code
150	16.2	16.5	21.5	30.9	5	34	11	17	17	79	MGALS-233	MG-300H
185	10.2	18.5	24	34.6	5.5	36	12	18	18	84	MGALS-311	MG-300H
185	12.7	18.5	24	34.6	5.5	36	12	18	18	84	MGALS-234	MG-300H
185	16.2	18.5	24	34.6	5.5	36	12	18	18	84	MGALS-235	MG-300H
225	12.7	21	27	39	6	40	14	20	20	94	MGALS-320	MG-300H
240	12.7	21.3	28.2	40.6	6.6	44	14	22	22	102	MGALS-236	MG-300H
240	16.2	21.3	28.2	40.6	6.6	44	14	22	22	102	MGALS-237	MG-300H
300	16.2	24.1	31.2	44.2	7.0	47	14	27	27	115	MGALS-300	MG-300H
300	20.3	24.1	31.2	44.2	7	47	14	27	27	115	MGALS-259	MG-300H
400	20.3	27.1	35.7	51.5	8.5	56	13	31	30	130	MGALS-260	MG-1000
500	20.3	30.2	41	58.7	10	60	15	33	32	140	MGALS-296	MG-1000
625	20.3	35.2	46	66	10	69	16	35	34	154	MGALS-261	MG-1000
800	BL	39	51	73	12	77	25	39	39	180	MGALS-318	MG-1000
1000	BL	43.5	57	81.9	13.5	100	30	45	45	220	MGALS-319	MG-1000

*All dimensions are
in mm