



Bullet Male

**Bullet
Male**



Technical Specification

Material: Brass

Surface: Tin-plated to protect against corrosion

Minimum operating temperature: -20 °C

Maximum operating temperature: 80 °C

Reference standard: Indian Standards

Features

- Annealed material optimizes material and crimping properties
- ETP Electrolytic Grade Copper.
- Tin-plated 5 micron plus to protect against corrosion.
- Crack free crimping.
- Bur free connection surface.
- Lowest millivolt drop for DC current application.
- Simple and safe connection.
- Terminate power cables in high-voltage applications.
- Provided with inspection hole to ensure the conductor has been fully inserted before crimping is

Bullet Male

	done. Flat contact surface to avoid hotspot.
--	--

BULLET MALE TERMINALS



MG CAT No.	TAB Size mm	Cable Size mm2	Description	L	H	W	APPLIC- ABLE MATING TERMINAL	MATE- RIAL	"STD PACKING QTY.(NOS) CHAIN"
MG-1808	Φ 3.96	0.75 - 1.5	Bullet Male (CA-104)	17.08	N.A.	3.96	1825	BRASS	7,000
MG-1708	Φ 3.96	0.5 - 1.0	1808 Small (CA-104)	17.08	N.A.	3.96	1825	BRASS	7,000

*All dimensions are in mm